

LORO-X Steel Discharge Pipes with new LORO-XVAC Sealing Element

DN 40 = Art.-No. 00918.040X
DN 50 = Art.-No. 00918.050X
DN 70 = Art.-No. 00918.070X

now also for Vacuum WC Systems




For the use of LORO-X steel discharge pipes with the proven LORO-X plug-in sleeve connections in vacuum systems, LOROWERK has developed a new LORO-XVAC sealing element made of EPDM with nominal diameters of 40, 50 and 70.

That way, the advantages of the LORO-X and LORO-XVAC sealing elements have been combined in one special sealing element for vacuum operation.

Advantages:

- Vacuum resistance in conformity with standards
- No noise and shock transmission
- No metallic connection
- No glue required
- Reduction of stocks
- Higher flexibility and broader application range of the LORO-X steel discharge piping system
- To be laid just like the LORO-X sealing element

Available System Components



Approval certificates issued. Inquire at the manufacturer's plant please

Technical staats:
 June 2018.
 Subject to technical changes

	DN	40	50	70
— Pipes with one socket				
— Pipes with two sockets		•	•	•
— Branches		•	•	•
∩ Bends		•	•	•
△ Transition pipes		•	•	•
⊥ Socket pieces		•	•	•
⊥ Deck and wall sockets		•	•	•
⊥ Deck sockets for Vacuum WC		-	•	-
⊥ Spezial connection pieces with flange		•	•	•
⊥ XVAC sealing elements		•	•	•
⊥ Pipe clamps		•	•	•

LOROWERK K.H.Vahlbrauk GmbH & Co.KG

Kriegerweg 1, 37581 Bad Gandersheim,
 Tel.: +49 53 82.710, Fax: +49 53 82.712 03
 Internet: www.loro-x.com, e-mail: infocenter@lorowerk.de