

LORO-X PIPE WITH 2 SOCKET WITHOUT 40

INTERNAL COATING 3000 MM DN

LORO-X pipe 2 joints without internal coating 3000 mm DN 40

Kuvaus

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard with 2-chamber push-fit socket connection, for filling and ventilating pipes, building material class A1, dimensionally stable, break-proof, backflow-safe, without inside coating, 3000 mm with 2sockets, DN40




Tuotetiedot

EAN-koodi	4038088042922
ETIM-luokka	EC011386
Nimellishalkaisija	DN 40
Nimellispituus/-aste	3000
Ulkomitat (KxLxS)	51 x 51 x 3000 mm
Paino	4,70 Kg (STK)
Tuoteryhmä	5
Tullitariffin numero	73063012
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

LORO-X Rohre mit 2 Muffen aus Stahl, feuerverzinkt, ohne Innenbeschichtung. Alternativ können gemäß DIBt auch Formteile mit Innenbeschichtung verwendet werden.



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

[Hyväksyntä \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Mittapiirustus \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Esite \(PDF\)](#)

[CAD \(DWG\)](#)