

LORO-X PIPE WITH 2 SOCKET 3000 MM DN 100

LORO-X pipe 2 sockets 3000 mm DN 100

Popis

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 3000 mm with 2sockets, DN100




Údaje o artiklu

EAN kód	4038088004678
ETIM třída	EC011386
Jmenovitý průměr	DN 100
Jmenovitá délka/stupeň	3000
Vnější rozměry (VxŠxD)	118 x 118 x 3000 mm
Hmotnost	16,30 Kg (STK)
Skupina produktů	1
Celní sazebník	73063012
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

LORO-X Stahlabflussrohre mit 2 Muffen werden hauptsächlich für die bauseitige Erstellung von Passstücken verwendet und eignen sich daher auch gut für Lagerhaltung. Wird das Rohr mit 2 Muffen an der benötigten Länge getrennt, so kann die andere Seite ebenfalls als Rohr mit 1 Muffe verwendet werden. Verschnitt wird so minimiert.



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)
[Certifikát \(PDF\)](#)
[BIM IFC4 \(parametrisch\)](#)

[Výkres rozměrů \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Prospekt \(PDF\)](#)
[CAD \(DWG\)](#)