

LORO-X PIPE WITH 2 SOCKET WITHOUT 50

INTERNAL COATING 2000 MM DN

LORO-X pipe 2 joints without internal coating 2000 mm DN 50

Descrição

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard with 2-chamber push-fit socket connection, for filling and ventilating pipes, building material class A1, dimensionally stable, break-proof, backflow-safe, without inside coating, 2000 mm with 2sockets, DN50




Dados do artigo

Código EAN	4038088042915
Classe ETIM	EC011386
Diâmetro nominal	DN 50
Comprimento/grau nominal	2000
Medidas exteriores (AxLxP)	63 x 63 x 2000 mm
Peso	4,10 Kg (STK)
Grupo de produtos	5
Número de pauta aduaneira	73063012
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

LORO-X Rohre mit 2 Muffen aus Stahl, feuerverzinkt, ohne Innenbeschichtung. Alternativ können gemäß DIBt auch Formteile mit Innenbeschichtung verwendet werden.



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[Homologação \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Desenho cotado \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochura \(PDF\)](#)

[CAD \(DWG\)](#)