

LORO-X PIPE WITH 2 SOCKET 750 MM DN 50

LORO-X pipe 2 sockets 750 mm DN 50

Descrizione

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 750 mm with 2sockets, DN50




Dati articolo

Codice EAN	4038088006337
Classe ETIM	EC011386
Diametro nominale	DN 50
Lunghezza/grado nominale	750
Misure esterne (AxLxP)	63 x 63 x 750 mm
Peso	1,50 Kg (STK)
Gruppo prodotti	1
Numero tariffa doganale	73063012
Materiale / Colore	Stahl feuerverzinkt, Silber

Note d'uso

LORO-X Stahlabflussrohr mit 2 Muffen werden hauptsächlich für die bauseitige Erstellung von Passstücken verwendet und eignen sich daher auch gut für Lagerhaltung. Wird das Rohr mit 2 Muffen an der benötigten Länge getrennt, so kann die andere Seite ebenfalls als Rohr mit 1 Muffe verwendet werden. Verschnitt wird so minimiert.



Download



Alles online

[Istruzioni di installazione \(PDF\)](#)

[Certificato \(PDF\)](#)

[BIM IFC4 \(parametric\)](#)

[Disegno dimensionale \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)

[CAD \(DWG\)](#)