

LORO-X PIPE WITH 2 SOCKET 750 MM DN 80

LORO-X pipe 2 sockets 750 mm DN 80

Opis

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 750 mm with 2sockets, DN 80




Dane artykułu

Kod EAN	4038088037942
Klasa ETIM	EC011386
Średnica nominalna	DN 80
Długość/stopień nominalny	750
Wymiary zewnętrzne (WxSxD)	102 x 102 x 750 mm
Waga	3,00 Kg (STK)
Grupa produktów	1
Numer taryfy celnej	73063012
Materiał / Kolor	Stahl feuerverzinkt, Silber

Wskazówki dotyczące użytkowania

LORO-X Stahlabflussrohre mit 2 Muffen werden hauptsächlich für die bauseitige Erstellung von Passstücken verwendet und eignen sich daher auch gut für Lagerhaltung. Wird das Rohr mit 2 Muffen an der benötigten Länge getrennt, so kann die andere Seite ebenfalls als Rohr mit 1 Muffe verwendet werden. Verschnitt wird so minimiert.



Pobieranie



Alles online

[Instrukcja montażu \(PDF\)](#)
[Certyfikat \(PDF\)](#)
[BIM IFC4 \(parametryczny\)](#)
[Rysunek wymiarowy \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[Broszura \(PDF\)](#)
[CAD \(DWG\)](#)