


LORO-X PIPE WITH 2 SOCKET WITHOUT 50

INTERNAL COATING 500 MM DN

LORO-X pipe 2 joints without internal coating 500 mm DN 50

Description

LORO-X pipe, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 500 mm with 2sockets, DN50



Article information

EAN Code	4038088042830
ETIM Class	EC011386
Nominal diameter	DN 50
Nominal length/degree	500
Outside measurements (HxWxL)	63 x 63 x 500 mm
Weight	1,00 Kg (STK)
Product group	5
Customs tariff number	73063012
Material / Color	Stahl feuerverzinkt, Silber

Usage note

LORO-X Rohre mit 2 Muffen aus Stahl, feuerverzinkt, ohne Innenbeschichtung. Alternativ können gemäß DIBt auch Formteile mit Innenbeschichtung verwendet werden.

Downloads



Alles online

[Installation \(PDF\)](#)

[Certificate \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[CAD drawing \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)

[CAD \(DWG\)](#)