


LORO COPPER BRANCH 87 DEGREE DN 70/70

LORO-X branch copper 87 degrees DN 70/70

Description

LORO-N branch, made of copper, in accordance with DIN 1754/1786, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, 87 degrees, DN70



Données de l'article

Code EAN	4038088034453
Classe ETIM	EC003025
Diamètre nominal	DN 70, DN 70
Longueur/degré nominal	87
Dimensions extérieures (HxLxP)	84 x 164 x 230 mm
Poids	1,00 Kg (STK)
Groupe de produits	1
Numéro tarifaire douanier	74121000
Matériau / Couleur	Kupfer, Kupfer

Note d'utilisation

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM IFC4 \(paramétrisch\)](#)

[Dessin dimensionnel \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[BIM 3D \(STEP\)](#)