


LORO-X BRANCH 70 DEGREE DN 40/40

LORO-X branch 70 degrees DN 40/40

Descripción

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 70 degrees, DN40



Datos del artículo

Código EAN	4038088013342
Clase ETIM	EC003025
Diámetro nominal	DN 40, DN 40
Longitud/grado nominal	70
Medidas exteriores (AxAxL)	51 x 109 x 140 mm
Peso	0,30 Kg (STK)
Grupo de productos	1
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[Certificado \(PDF\)](#)

BIM 3D (STEP)

[Dibujo dimensional \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Folleto \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)