

LORO-X BRANCH 70 DEGREE DN 50/50

LORO-X branch 70 degrees DN 50/50

Descripción

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 70 degrees, DN50




Datos del artículo

Código EAN	4038088013366
Clase ETIM	EC003025
Diámetro nominal	DN 50, DN 50
Longitud/grado nominal	70
Medidas exteriores (AxAxL)	63 x 134 x 168 mm
Peso	0,50 Kg (STK)
Grupo de productos	1
Número de arancel aduanero	73089098
Material / Color	Stahl feuerverzinkt, Silber

Nota de uso

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300



Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

Certificado (PDF)

BIM 3D (STEP)

[Dibujo dimensional \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Folleto \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)