


LORO-X BRANCH 70 DEGREE DN 100/100

LORO-X branch 70 degrees DN 100/100

Descrizione

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 70 degrees, DN100



Date article

Cod EAN	4038088013397
Clasă ETIM	EC003025
Diametru nominal	DN 100, DN 100
Lungime/grad nominal	70
Dimensiuni exterioare (ÎxLxA)	118 x 247 x 300 mm
Greutate	2,40 Kg (STK)
Grupă de produse	1
Număr tarif vamal	73089098
Material / Culoare	Stahl feuerverzinkt, Silber

Notă de utilizare

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Descărcări



Alles online

[Instrucțiuni de montaj \(PDF\)](#)

[Certificat \(PDF\)](#)

BIM 3D (STEP)

[Desen CAD \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Brosură \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)