


LORO-X BRANCH 70 DEGREE DN 125/125

LORO-X branch 70 degrees DN 125/125

Descrição

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 70 degrees, DN125



Dados do artigo

Código EAN	4038088013403
Classe ETIM	EC003025
Diâmetro nominal	DN 125, DN 125
Comprimento/grau nominal	70
Medidas exteriores (AxLxP)	152 x 308 x 360 mm
Peso	4,20 Kg (STK)
Grupo de produtos	1
Número de pauta aduaneira	73089098
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[Homologação \(PDF\)](#)

BIM 3D (STEP)

[Desenho cotado \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Brochura \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)