
LORO-X BRANCH 45 DEGREE DN 40/40

LORO-X branch 45 degrees DN 40/40

Beskrivelse

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN40





Artikkeldata

EAN-kode	4038088013489
ETIM-klasse	EC003025
Nominell diameter	DN 40, DN 40
Nominell lengde/grad	45
Utvendige mål (HxBxL)	51 x 113 x 113 mm
Vekt	0,40 Kg (STK)
Produktgruppe	1
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Nedlastinger

Alles online

Monteringsanvisning (PDF)
Godkjenning (PDF)
BIM 3D (STEP)
Måltegning (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Brosjyre (PDF)
CAD 3D (DWG)
BIM 3D (IFC)