


LORO COPPER BRANCH 45 DEGREE DN 100/100

LORO-X branch copper 45 degrees DN 100/100

Descripción

LORO-N branch, made of copper, in accordance with DIN 1754/1786, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, 45 degrees, DN100



Datos del artículo

Código EAN	4038088034507
Clase ETIM	EC003025
Diámetro nominal	DN 100, DN 100
Longitud/grado nominal	45
Medidas exteriores (AxAxL)	118 x 257 x 355 mm
Peso	2,70 Kg (STK)
Grupo de productos	1
Número de arancel aduanero	74121000
Material / Color	Kupfer, Kupfer

Nota de uso

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Dibujo dimensional \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM 3D \(IFC\)](#)

[Folleto \(PDF\)](#)

[BIM 3D \(STEP\)](#)