


LORO-X BRANCH 45 DEGREE DN 32/32

LORO-X branch 45 degrees DN 32/32

Описание

LORO-X branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN32



Данни за артикула

ЕАН код	4038088013595
ЕТИМ клас	EC003025
Номинален диаметър	DN 32, DN 32
Номинална дължина/градус	45
Външни размери (ВxШxД)	39 x 89 x 110 mm
Тегло	0,20 Kg (STK)
Продуктова група	1
Митнически тарифен номер	73089098
Материал / Цвят	Stahl feuerverzinkt, Silber

Забележка за употреба

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300

Изтегляния



Alles online

[Инструкция за монтаж \(PDF\)](#)
[Сертификат \(PDF\)](#)
[BIM IFC4 \(parametrisch\)](#)

[CAD чертеж \(PDF\)](#)
[CAD 2D \(DXF\)](#)

[Брошура \(PDF\)](#)
[CAD \(DWG\)](#)