

LORO COPPER BRANCH 45 DEGREE DN 80/80

LORO-X branch copper 45 degrees DN 80/80

Description

LORO-N branch, made of copper, in accordance with DIN 1754/1786, with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, 45 degrees, DN 80




Article information

EAN Code	4038088034491
ETIM Class	EC003025
Nominal diameter	DN 80, DN 80
Nominal length/degree	45
Outside measurements (HxWxL)	103 x 226 x 295 mm
Weight	1,50 Kg (STK)
Product group	1
Customs tariff number	74121000
Material / Color	Kupfer, Kupfer

Usage note

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300



Downloads



Alles online

[Installation \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[CAD drawing \(PDF\)](#)

[CAD \(DWG\)](#)

[Brochure \(PDF\)](#)

[BIM IFC4 \(parametrisch\)](#)