


LORO-X REDUCED BRANCH 45 DEGREE DN 50/40

LORO-X reduced branch 45 degrees DN 50/40

Opis

LORO-X reducing branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN50/40



Podaci o artiklu

EAN kod	4038088014356
ETIM klasa	EC003025
Nazivni promjer	DN 50, DN 40
Nazivna duljina/stupanj	45
Vanjske mjere (VxŠxD)	63 x 126 x 168 mm
Težina	0,50 Kg (STK)
Grupa proizvoda	1
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300. Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr. Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

Certifikat (PDF)

[Dimenzijski crtež \(PDF\)](#)

CAD 2D (DXF)

[Prospekt \(PDF\)](#)

CAD (DWG)