
LORO-X REDUCED BRANCH 45 DEGREE DN 100/40

LORO-X reduced branch 45 degrees DN 100/40

Descrição

LORO-X reducing branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN100/40





Dados do artigo

Código EAN	**4038088014394**
Classe ETIM	**EC003025**
Diâmetro nominal	**DN 100, DN 40**
Comprimento/grau nominal	**45**
Medidas exteriores (AxLxP)	**118 x 179 x 250 mm**
Peso	**1,50 Kg (STK)**
Grupo de produtos	**1**
Número de pauta aduaneira	**73089098**
Material / Cor	**Stahl feuerverzinkt, Silber**

Nota de utilização

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Transferências

Alles online

Instruções de instalação (PDF)
Homologação (PDF)
Desenho cotado (PDF)
CAD 2D (DXF)
Brochura (PDF)
CAD (DWG)