

LORO-X REDUCED BRANCH 45 DEGREE DN 150/125

LORO-X reduced branch 45 degrees DN 150/125

Descrição

LORO-X reducing branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN150/125




Dados do artigo

Código EAN	4038088014516
Classe ETIM	EC003025
Diâmetro nominal	DN 150, DN 125
Comprimento/grau nominal	45
Medidas exteriores (AxLxP)	181 x 358 x 420 mm
Peso	6,20 Kg (STK)
Grupo de produtos	1
Número de pauta aduaneira	73089098
Material / Cor	Stahl feuerverzinkt, Silber

Nota de utilização

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300. Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr. Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.



Transferências



Alles online

[Instruções de instalação \(PDF\)](#)

[Homologação \(PDF\)](#)

[Desenho cotado \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochura \(PDF\)](#)

[CAD \(DWG\)](#)