LORO-X DOUBLE BRANCH 87 DEGREE DN 50/50/50

LORO-X double branch 87 degrees DN 50/50/50

Beskrivningstext

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN50/50/50



Artikeldata

EAN-kod	**4038088014820**
ETIM-klass	**EC003026**
Nominell diameter	**DN 50, DN 50, DN 50**
Nominell längd/grad	**87**
Yttermått (HxBxL)	**63 x 179 x 168 mm**
Vikt	**0,70 Kg (STK)**
Produktgrupp	**1**
Tullnummer	**73089098**
Material / Färg	**Stahl feuerverzinkt, Silber**

Användningsanvisning

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Nedladdningar

Alles online

Monteringsanvisning (PDF)
Måttritning (PDF)
Broschyr (PDF)
Godkännande (PDF)
CAD 2D (DXF)
CAD 3D (DWG)
BIM 3D (STEP)
BIM IFC4 (parametrisch)
BIM 3D (IFC)