LORO-X DOUBLE BRANCH 87 DEGREE DN 125/125/125

LORO-X double branch 87 degrees DN 125/125/125

Besedilo za popis del

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN125/125/125

Podatki o izdelku

EAN koda	4038088014929
ETIM razred	EC003026
Nazivni premer	DN 125, DN 125, DN 125
Nazivna dolžina/stopinja	87
Zunanje mere (VxŠxD)	152 x 397 x 360 mm
Teža	5,60 Kg (STK)
Skupina izdelkov	1
Carinska tarifna številka	73089098
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Prenosi

Alles online

Navodila za vgradnjo (PDF)
BIM IFC4 (parametrisch)
Prospekt (PDF)
Certifikat (PDF)