LORO-X DOUBLE BRANCH 87 DEGREE DN 125/125/125

LORO-X double branch 87 degrees DN 125/125/125

Texto de licitación

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN125/125/125

Datos del artículo

Código EAN	**4038088014929**
Clase ETIM	**EC003026**
Diámetro nominal	**DN 125, DN 125, DN 125**
Longitud/grado nominal	**87**
Medidas exteriores (AxAxL)	**152 x 397 x 360 mm**
Peso	**5,60 Kg (STK)**
Grupo de productos	**1**
Número de arancel aduanero	**73089098**
Material / Color	**Stahl feuerverzinkt, Silber**

Nota de uso

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Descargas

Instrucciones de instalación (PDF)
Folleto (PDF)
Certificado (PDF)
BIM IFC4 (parametrisch)

Alles online