LORO-X DOUBLE BRANCH 87 DEGREE DN 150/150/150

LORO-X double branch 87 degrees DN 150/150/150

Besedilo za popis del

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN150/150/150

Podatki o izdelku

EAN koda	4038088014974
ETIM razred	EC003026
Nazivni premer	DN 150, DN 150, DN 150
Nazivna dolžina/stopinja	87
Zunanje mere (VxŠxD)	181 x 439 x 400 mm
Teža	7,90 Kg (STK)
Skupina izdelkov	1
Carinska tarifna številka	73089098
Material / Barva	Stahl feuerverzinkt, Silber

Opomba za uporabo

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Prenosi

Alles online

Navodila za vgradnjo (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
Prospekt (PDF)
CAD 3D (DWG)
Certifikat (PDF)
BIM IFC4 (parametrisch)