LORO-X DOUBLE BRANCH 87 DEGREE DN 150/150/150

LORO-X double branch 87 degrees DN 150/150/150

Bestektekst

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN150/150/150

Artikelgegevens

EAN-code	**4038088014974**
ETIM Klasse	**EC003026**
Nominale diameter	**DN 150, DN 150, DN 150**
Nominale lengte/graad	**87**
Buitenafmetingen (HxBxL)	**181 x 439 x 400 mm**
Gewicht	**7,90 Kg (STK)**
Productgroep	**1**
Douanetariefnummer	**73089098**
Materiaal / Kleur	**Stahl feuerverzinkt, Silber**

Gebruiksaanwijzing

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Downloads

Alles online

Installatiehandleiding (PDF)
CAD 2D (DXF)
BIM 3D (IFC)
Brochure (PDF)
CAD 3D (DWG)
Certificaat (PDF)
BIM IFC4 (parametrisch)