LORO-X DOUBLE BRANCH 87 DEGREE DN 150/150/150

LORO-X double branch 87 degrees DN 150/150/150

Texte de prescription

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN150/150/150

Données de l'article

Code EAN	**4038088014974**
Classe ETIM	**EC003026**
Diamètre nominal	**DN 150, DN 150, DN 150**
Longueur/degré nominal	**87**
Dimensions extérieures (HxLxP)	**181 x 439 x 400 mm**
Poids	**7,90 Kg (STK)**
Groupe de produits	**1**
Numéro tarifaire douanier	**73089098**
Matériau / Couleur	**Stahl feuerverzinkt, Silber**

Note d'utilisation

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Téléchargements

Alles online

Notice d'installation (PDF)
Brochure (PDF)
Certificat (PDF)
CAD 2D (DXF)
CAD 3D (DWG)
BIM IFC4 (parametrisch)
BIM 3D (IFC)