LORO-X DOUBLE BRANCH 87 DEGREE DN 80/80/80

LORO-X double branch 87 degrees DN 80/80/80

Beskrivningstext

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN80/80/80

Artikeldata

EAN-kod	4038088089545
ETIM-klass	EC003026
Nominell diameter	DN 80, DN 80, DN 80
Nominell längd/grad	87
Yttermått (HxBxL)	102 x 278 x 265 mm
Vikt	1,90 Kg (STK)
Produktgrupp	1
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Nedladdningar

Alles online

Monteringsanvisning (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Broschyr (PDF)
CAD 3D (DWG)
BIM 3D (IFC)
Godkännande (PDF)
BIM 3D (STEP)