LORO-X DOUBLE BRANCH 87 DEGREE DN 80/80/80

LORO-X double branch 87 degrees DN 80/80/80

Kiírási szöveg

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN80/80/80

Cikkadatok

EAN kód	4038088089545
ETIM osztály	EC003026
Névleges átmérő	DN 80, DN 80, DN 80
Névleges hossz/fok	87
Külső méretek (MxSzxH)	102 x 278 x 265 mm
Súly	1,90 Kg (STK)
Termékcsoport	1
Vámtarifaszám	73089098
Anyag / Szín	Stahl feuerverzinkt, Silber

Használati megjegyzés

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Letöltések

Alles online

Szerelési útmutató (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Prospektus (PDF)
CAD 3D (DWG)
BIM 3D (IFC)
Engedély (PDF)
BIM 3D (STEP)