LORO-X DOUBLE BRANCH 87 DEGREE DN 80/80/80

LORO-X double branch 87 degrees DN 80/80/80

Text pre výberové konanie

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN80/80/80

Údaje o artikli

EAN kód	4038088089545
ETIM trieda	EC003026
Menovitý priemer	DN 80, DN 80, DN 80
Menovitá dĺžka/stupeň	87
Vonkajšie rozmery (VxŠxH)	102 x 278 x 265 mm
Hmotnosť	1,90 Kg (STK)
Skupina produktov	1
Colný sadzobník	73089098
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Na stiahnutie

Alles online

Návod na montáž (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Prospekt (PDF)
CAD 3D (DWG)
BIM 3D (IFC)
Certifikát (PDF)
BIM 3D (STEP)