LORO-X DOUBLE BRANCH 45 DEGREE DN 50/50/50

LORO-X double branch 45 degrees DN 50/50/50

Beskrivelsestekst

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN50/50/50



Artikkeldata

EAN-kode	**4038088015780**
ETIM-klasse	**EC003026**
Nominell diameter	**DN 50, DN 50, DN 50**
Nominell lengde/grad	**45**
Utvendige mål (HxBxL)	**63 x 223 x 188 mm**
Vekt	**0,90 Kg (STK)**
Produktgruppe	**1**
Tolltariffnummer	**73089098**
Materiale / Farge	**Stahl feuerverzinkt, Silber**

Bruksanvisning

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Nedlastinger

Alles online

Monteringsanvisning (PDF)
Godkjenning (PDF)
BIM 3D (STEP)
Måltegning (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Brosjyre (PDF)
CAD 3D (DWG)
BIM 3D (IFC)