LORO-X DOUBLE BRANCH 45 DEGREE DN 125/125/125

LORO-X double branch 45 degrees DN 125/125/125

Udbudstekst

LORO-X double branch, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 45 degrees, DN125/125/125

Artikeldata

EAN-kode	**4038088015889**
ETIM Klasse	**EC003026**
Nominel diameter	**DN 125, DN 125, DN 125**
Nominel længde/grad	**45**
Ydermål (HxBxL)	**152 x 478 x 415 mm**
Vægt	**5,60 Kg (STK)**
Produktgruppe	**1**
Toldtarifnummer	**73089098**
Materiale / Farve	**Stahl feuerverzinkt, Silber**

Brugsanvisning

Die Buchstaben in den Artikelnummern von Abzweigen stehen für folgende Nennweiten: L = DN32, A = DN40, B = DN50, C = DN70, M = DN80, D = DN100, E = DN125, F = DN150, G = DN200, H = DN250, K = DN300.Bei LORO-X Abzweigen mit Reduktion steht die erste Nennweite für das gerade Rohrstück und die zweite Nennweite für das kleinere, darin mündende Abzweigrohr.Beispiel DN100/70: Ein DN70 Rohr mündet in ein DN100 Rohr in Fließrichtung.

Downloads

Alles online

Installationsvejledning (PDF)
CAD 2D (DXF)
BIM IFC4 (parametrisch)
Brochure (PDF)
CAD 3D (DWG)
BIM 3D (IFC)
Certifikat (PDF)
BIM 3D (STEP)