


## LORO-X BEND 87 DEGREE DN 125

### LORO-X bend 87 degrees DN 125

#### Descripción

LORO-X bend, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN125



#### Datos del artículo

|                            |                             |
|----------------------------|-----------------------------|
| Código EAN                 | 4038088018804               |
| Clase ETIM                 | EC003024                    |
| Diámetro nominal           | DN 125                      |
| Longitud/grado nominal     | 87                          |
| Medidas exteriores (AxAxL) | 152 x 242 x 264 mm          |
| Peso                       | 2,90 Kg (STK)               |
| Grupo de productos         | 1                           |
| Número de arancel aduanero | 73089098                    |
| Material / Color           | Stahl feuerverzinkt, Silber |

#### Nota de uso

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.

#### Descargas



Alles online

[Instrucciones de instalación \(PDF\)](#)

[Certificado \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[BIM Revit \(RFA\)](#)

[Dibujo dimensional \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Folleto \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM 3D \(IFC\)](#)