


## LORO-X BEND 15 DEGREE DN 80

LORO-X bend 15 degrees DN 80

### Beschrijving

LORO-X bend, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 15 degrees, DN 80



### Artikelgegevens

|                          |                             |
|--------------------------|-----------------------------|
| EAN-code                 | 4038088019535               |
| ETIM Klasse              | EC003024                    |
| Nominale diameter        | DN 80                       |
| Nominale lengte/graad    | 15                          |
| Buitenafmetingen (HxBxL) | 102 x 125 x 234 mm          |
| Gewicht                  | 0,91 Kg (STK)               |
| Productgroep             | 1                           |
| Douanetariefnumme        | 73089098                    |
| r                        |                             |
| Materiaal / Kleur        | Stahl feuerverzinkt, Silber |

### Gebruiksaanwijzing

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.

### Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[Certificaat \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Maattekening \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM IFC4 \(parametrisch\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM 3D \(IFC\)](#)