

LORO-X BEND 15 DEGREE DN 100

LORO-X bend 15 degrees DN 100

Kuvaus

LORO-X bend, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 15 degrees, DN100




Tuotetiedot

EAN-koodi	4038088019542
ETIM-luokka	EC003024
Nimellishalkaisija	DN 100
Nimellispituus/-aste	15
Ulkomitat (KxLxS)	118 x 133 x 219 mm
Paino	1,20 Kg (STK)
Tuoteryhmä	1
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.



Lataukset



Alles online

[Asennusohje \(PDF\)](#)

Hvväksyntä (PDF)

BIM 3D (STEP)

BIM Revit (RFA)

[Mittapiirustus \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Esite \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)