


LORO-X BEND 15 DEGREE DN 200

LORO-X bend 15 degrees DN 200

Popis

LORO-X bend, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 15 degrees, DN200



Údaje o artikli

EAN kód	4038088019573
ETIM trieda	EC003024
Menovitý priemer	DN 200
Menovitá dĺžka/stupeň	15
Vonkajšie rozmery (VxŠxH)	247 x 267 x 355 mm
Hmotnosť	5,20 Kg (STK)
Skupina produktov	1
Colný sadzovník	73089098
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.

Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

[Certifikát \(PDF\)](#)

BIM 3D (STEP)

[Rozmerový výkres \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Prospekt \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)