


LORO-X SHORT RADIUS BEND 87 DEGREE DN 70

LORO-X bend with narrow radius 87 degrees DN 70

Opis

LORO-X bend with short radius, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN70



Dane artykułu

Kod EAN	4038088019610
Klasa ETIM	EC003024
Średnica nominalna	DN 70
Długość/stożek nominalny	87
Wymiary zewnętrzne (WxSxD)	84 x 152 x 165 mm
Waga	0,70 Kg (STK)
Grupa produktów	1
Numer taryfy celnej	73089098
Materiał / Kolor	Stahl feuerverzinkt, Silber

Wskazówki dotyczące użytkowania

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.

Pobieranie



Alles online

[Instrukcja montażu \(PDF\)](#)

[Certyfikat \(PDF\)](#)

BIM 3D (STEP)

[Rysunek wymiarowy \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Broszura \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)