


LORO-X SHORT RADIUS BEND 87 DEGREE DN 70

LORO-X bend with narrow radius 87 degrees DN 70

Beskrivelse

LORO-X bend with short radius, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 87 degrees, DN70



Artikkeldata

EAN-kode	4038088019610
ETIM-klasse	EC003024
Nominell diameter	DN 70
Nominell lengde/grad	87
Utvendige mål (HxBxL)	84 x 152 x 165 mm
Vekt	0,70 Kg (STK)
Produktgruppe	1
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.

Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

Godkjenning (PDF)

BIM 3D (STEP)

[Måltegning \(PDF\)](#)

CAD 2D (DXF)

BIM IFC4 (parametrisch)

[Brosjyre \(PDF\)](#)

CAD 3D (DWG)

BIM 3D (IFC)