

LORO-X OFFSET BEND 130 MM DN 50

LORO-X offset bend 130 mm DN 50

Opis

LORO-X offset bend made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, offset 130 mm, DN50




Podaci o artiklu

EAN kod	4038088019917
ETIM klasa	EC003024
Nazivni promjer	DN 50
Vanjske mjere (VxŠxD)	63 x 188 x 318 mm
Težina	0,80 Kg (STK)
Grupa proizvoda	1
Carinski tarifni broj	73089098
Materijal / Boja	Stahl feuerverzinkt, Silber

Napomena za upotrebu

Durch den Versprung ist der Etagenbogen z.B. bei Falleleitungen zur Überbrückung von Mauer- und Putzvorsprüngen bestens geeignet.



Preuzimanja



Alles online

[Upute za ugradnju \(PDF\)](#)

[Certifikat \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Dimenzijski crtež \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Prospekt \(PDF\)](#)

[CAD 3D \(DWG\)](#)