

LORO-X OFFSET BEND 75 MM DN 125

LORO-X offset bend 75 mm DN 125

Popis

LORO-X offset bend made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, offset 75 mm, DN125




Údaje o artiklu

EAN kód	4038088020067
ETIM třída	EC003024
Jmenovitý průměr	DN 125
Vnější rozměry (VxŠxD)	152 x 218 x 330 mm
Hmotnost	3,30 Kg (STK)
Skupina produktů	1
Celní sazebník	73089098
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

Durch den Versprung ist der Etagenbogen z.B. bei Falleitungen zur Überbrückung von Mauer- und Putzvorsprüngen bestens geeignet.



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)

[Certifikát \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Výkres rozměrů \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Prospekt \(PDF\)](#)

[CAD 3D \(DWG\)](#)