

LORO-X REDUCING ANGLE BEND 90 DEGREE DN 50

LORO-X elbow reduced with standard socket DN 50/40

Popis

LORO-X angle bend, made of steel, hot-dip galvanized, reduced, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 90 degrees, DN50/40




Údaje o artiklu

EAN kód	4038088022740
ETIM třída	EC003024
Jmenovitý průměr	DN 50, DN 40
Jmenovitá délka/stupeň	90
Vnější rozměry (VxŠxD)	63 x 92 x 126 mm
Hmotnost	0,30 Kg (STK)
Skupina produktů	1
Celní sazebník	73089098
Materiál / Barva	Stahl feuerverzinkt, Silber

Pokyny k použití

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.



Ke stažení



Alles online

[Návod k instalaci \(PDF\)](#)

[Certifikát \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Výkres rozměrů \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Prospekt \(PDF\)](#)

[CAD 3D \(DWG\)](#)