

LORO-X ANGLE BEND WITH SHORT SOCKET

90 DEGREE DN 50

LORO-X elbow with short socket DN 50

Kuvaus

LORO-X angle bend made of steel, hot-dip galvanized, with short socket, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 90 degrees, DN50




Tuotetiedot

EAN-koodi	4038088022832
ETIM-luokka	EC003024
Nimellishalkaisija	DN 50
Nimellispituus/-aste	90
Ulkomitat (KxLxS)	63 x 92 x 132 mm
Paino	0,30 Kg (STK)
Tuoteryhmä	1
Tullitariffin numero	73089098
Materiaali / Väri	Stahl feuerverzinkt, Silber

Käyttöohje

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.



Lataukset



Alles online

[Asennusohje \(PDF\)](#)
[Hyväksyntä \(PDF\)](#)
[BIM 3D \(STEP\)](#)
[Mittapiirustus \(PDF\)](#)
[CAD 2D \(DXF\)](#)
[BIM IFC4 \(parametrisch\)](#)
[Esite \(PDF\)](#)
[CAD 3D \(DWG\)](#)
[BIM 3D \(IFC\)](#)