


LORO-X ANGLE BEND WITH SHORT SOCKET

90 DEGREE DN 50

LORO-X elbow with short socket DN 50

Description

LORO-X angle bend made of steel, hot-dip galvanized, with short socket, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, 90 degrees, DN50



Données de l'article

Code EAN	4038088022832
Classe ETIM	EC003024
Diamètre nominal	DN 50
Longueur/degré nominal	90
Dimensions extérieures (HxLxP)	63 x 92 x 132 mm
Poids	0,30 Kg (STK)
Groupe de produits	1
Numéro tarifaire douanier	73089098
Matériau / Couleur	Stahl feuerverzinkt, Silber

Note d'utilisation

Bei Verwendung von Sicherungsschellen am Spitzende des Bogens ist teilweise die Variante mit Ausklinkung zu verwenden.

Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

[Certificat \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Dessin dimensionnel \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM IFC4 \(paramétrisch\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM 3D \(IFC\)](#)