

LORO-X DOUBLE SOCKET DN 50

LORO-X double socket DN 50

Opis

LORO-X double socket, made of steel, hot-dip galvanized, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN50




Dane artykułu

Kod EAN	4038088024317
Klasa ETIM	EC003024
Średnica nominalna	DN 50
Wymiary zewnętrzne (WxSxD)	63 x 63 x 94 mm
Waga	0,20 Kg (STK)
Grupa produktów	1
Numer taryfy celnej	73089098
Materiał / Kolor	Stahl feuerverzinkt, Silber

Wskazówki dotyczące użytkowania

Sollte nach dem Ablängen ein Rohrstück ohne Muffe anfallen, so kann es durch die LORO-X Doppelmuffe wieder zu einem Muffenrohr ergänzt werden. Die Doppelmuffe sollte auf das Restrohr mit dem LORO-X Dichtelement und dem LORO-X Kleber aufgeklebt werden. (In frostgefährdeten Bereichen sind gegen die Fließrichtung gerichtete Muffen, auch Doppelmuffen, nicht zulässig)



Pobieranie



Alles online

[Instrukcja montażu \(PDF\)](#)

[Certyfikat \(PDF\)](#)

[Rysunek wymiarowy \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Broszura \(PDF\)](#)

[CAD \(DWG\)](#)