

LORO-X TRANSITION PIPE ECCENTRIC DN 40/50

LORO-X eccentric transition pipe DN 40/50

Beschrijving

LORO-X transition pipe, made of steel, hot-dip galvanized, eccentric, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN40/50




Artikelgegevens

EAN-code	4038088027424
ETIM Klasse	EC003024
Nominale diameter	DN 40, DN 50
Buitenafmetingen (HxBxL)	58 x 53 x 140 mm
Gewicht	0,30 Kg (STK)
Productgroep	1
Douanetariefnummer	73089098

Materiaal / Kleur **Stahl feuerverzinkt, Silber**

Gebruiksaanwijzing

Gemäß EN 12056-3 7.6.1 ist bei Aufweitung in nahezu waagrecht verlegten Leitungen auf Rohrscheitelgleichheit zu achten. Die Aufweitung soll also exzentrisch "nach unten" erfolgen.



Downloads



Alles online

[Installatiehandleiding \(PDF\)](#)

[Certificaat \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Maattekening \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)