

## LORO-X TRANSITION PIPE CONCENTRIC WITH EXTENSION DN 50/100

LORO-X concentric transition pipe with extended spigot DN 50/100

### Beskrivelse

LORO-X transition pipe, made of steel, hot-dip galvanized, concentric, with extended peaked end, suitable for anchor clip art. no. 806X, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN50/100




### Artikkeldata

|                       |                             |
|-----------------------|-----------------------------|
| EAN-kode              | 4038088041857               |
| ETIM-klasse           | EC003024                    |
| Nominell diameter     | DN 50, DN 100               |
| Utvendige mål (HxBxL) | 102 x 102 x 223 mm          |
| Vekt                  | 1,00 Kg (STK)               |
| Produktgruppe         | 1                           |
| Tolltariffnummer      | 73089098                    |
| Materiale / Farge     | Stahl feuerverzinkt, Silber |

### Bruksanvisning

LORO-X Übergangsrohre (konzentrische Red.-Stücke) mit verlängertem Spitzende, passend für Sicherungsschelle Nr.806X



### Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkjenning \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Måltegning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brosjyre \(PDF\)](#)

[CAD 3D \(DWG\)](#)

[BIM Revit \(RFA\)](#)