

LORO-X ADAPTOR FROM PVC SOCKET TO LORO PIPE

LORO-X connection piece to KA-HT socket 50 DN 50

Popis

LORO-X connector made of steel, hot-dip galvanized, from LORO-X pipe DN50 to plastic pipe socket DN50, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN50




Údaje o artikli

EAN kód	4038088027585
ETIM trieda	EC003024
Menovitý priemer	DN 50
Vonkajšie rozmery (VxŠxH)	63 x 63 x 98 mm
Hmotnosť	0,20 Kg (STK)
Skupina produktov	1
Colný sadzobník	73089098
Materiál / Farba	Stahl feuerverzinkt, Silber

Pokyny na použitie

kein Verwendungshinweis notwendig



Na stiahnutie



Alles online

[Návod na montáž \(PDF\)](#)

[Certifikát \(PDF\)](#)

[BIM Revit \(RFA\)](#)

[Rozmerový výkres \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Prospekt \(PDF\)](#)

[CAD \(DWG\)](#)