

LORO-X ADAPTOR FROM PVC SOCKET TO LORO PIPE

LORO-X connection piece to KA-HT socket 50 DN 50

Description

LORO-X connector made of steel, hot-dip galvanized, from LORO-X pipe DN50 to plastic pipe socket DN50, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN50




Données de l'article

Code EAN	4038088027585
Classe ETIM	EC003024
Diamètre nominal	DN 50
Dimensions extérieures (HxLxP)	63 x 63 x 98 mm
Poids	0,20 Kg (STK)
Groupe de produits	1
Numéro tarifaire douanier	73089098
Matériau / Couleur	Stahl feuerverzinkt, Silber

Note d'utilisation

kein Verwendungshinweis notwendig



Téléchargements



Alles online

[Notice d'installation \(PDF\)](#)

[Certificat \(PDF\)](#)

[BIM Revit \(RFA\)](#)

[Dessin dimensionnel \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[Brochure \(PDF\)](#)

[CAD \(DWG\)](#)