

LX-ANSCHLUßST.M.KURZMU.A.KA-MU 70,DN 70

LORO-X connection piece with short socket to KA socket 70 DN 70

Opis

LORO-X connector with short socket made of steel, hot-dip galvanized, from LORO-X pipe DN70 to plastic pipe socket DN70, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN70/70




Dane artykułu

Kod EAN	4038088104774
Klasa ETIM	EC003024
Średnica nominalna	DN 70
Wymiary zewnętrzne (WxSxD)	84 x 84 x 87 mm
Waga	0,30 Kg (STK)
Grupa produktów	1
Numer taryfy celnej	73089098
Materiał / Kolor	Stahl feuerverzinkt, Silber

Wskazówki dotyczące użytkowania

kein Verwendungshinweis notwendig



Pobieranie



Alles online

[Instrukcja montażu \(PDF\)](#)

[Certyfikat \(PDF\)](#)

BIM 3D (STEP)

[Rysunek wymiarowy \(PDF\)](#)

CAD 2D (DXF)

BIM 3D (IFC)

[Broszura \(PDF\)](#)

CAD 3D (DWG)