

LX-ANSCHLUßST.M.KURZMU.A.KA-MU 100,

LORO-X connection piece with short sleeve to KA-socket 100 DN 100

Beskrivning

LORO-X connector with short socket made of steel, hot-dip galvanized, from LORO-X pipe DN100 to plastic pipe socket DN100, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN100/100




Artikeldata

EAN-kod	4038088104781
ETIM-klass	EC003024
Nominell diameter	DN 100
Ytermått (HxBxL)	118 x 118 x 98 mm
Vikt	0,50 Kg (STK)
Produktgrupp	1
Tullnummer	73089098
Material / Färg	Stahl feuerverzinkt, Silber

Användningsanvisning

kein Verwendungshinweis notwendig



Nedladdningar



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkännande \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Måttitning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Broschyr \(PDF\)](#)

[CAD 3D \(DWG\)](#)