

LX-ANSCHLUßST.M.KURZMU.A.KA-MU 100,

LORO-X connection piece with short sleeve to KA-socket 100 DN 100

Beskrivelse

LORO-X connector with short socket made of steel, hot-dip galvanized, from LORO-X pipe DN100 to plastic pipe socket DN100, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN100/100




Artikkeldata

EAN-kode	4038088104781
ETIM-klasse	EC003024
Nominell diameter	DN 100
Utvendige mål (HxBxL)	118 x 118 x 98 mm
Vekt	0,50 Kg (STK)
Produktgruppe	1
Tolltariffnummer	73089098
Materiale / Farge	Stahl feuerverzinkt, Silber

Bruksanvisning

kein Verwendungshinweis notwendig



Nedlastinger



Alles online

[Monteringsanvisning \(PDF\)](#)

[Godkjenning \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Måltegning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brosjyre \(PDF\)](#)

[CAD 3D \(DWG\)](#)