

LX-ANSCHLUßST.M.KURZMU.A.KA-MU.125,

LORO-X connection piece with short socket to KA socket 125 DN 125

Beskrivelse

LORO-X connector with short socket made of steel, hot-dip galvanized, from LORO-X pipe DN125 to plastic pipe socket DN125, in accordance with DIN EN 1123 with raised quality standard, with 2-chamber push-fit socket connection, building material class A1, dimensionally stable, break-proof, backflow-safe, long-life inside coating according to DIN EN ISO 2178 on the basis of a 2-component epoxy combination, colour: red-brown, DN125/125




Artikeldata

EAN-kode	4038088104798
ETIM Klasse	EC003024
Nominal diameter	DN 125
Ydermål (HxBxL)	151 x 151 x 130 mm
Vægt	1,10 Kg (STK)
Produktgruppe	1
Toldtarifnummer	73089098
Materiale / Farve	Stahl feuerverzinkt, Silber

Brugsanvisning

kein Verwendungshinweis notwendig



Downloads



Alles online

[Installationsvejledning \(PDF\)](#)

[Certifikat \(PDF\)](#)

[BIM 3D \(STEP\)](#)

[Måltægning \(PDF\)](#)

[CAD 2D \(DXF\)](#)

[BIM 3D \(IFC\)](#)

[Brochure \(PDF\)](#)

[CAD 3D \(DWG\)](#)